

Topper

- Optional LED Topper Sign
- Can accept custom inserts

Integrated Illuminated Sign

- High Visibility LED Sign
- Attract Customers

LCD Screen

- 10.2 inch wide 32-bit color
- Backlit TFT LCD panel
- 1280x800 Resolution
- 12 inch touch-screen (Optional)
- Customizable Ad Screens

Printer

- 56mm (2" standard)
- 80mm (3" optional)
- Graphics Capable with 3"

PIN Entry Device

- 16-key alphanumeric keypad
- PCI Certified
- Triple-DES (TDES) compliant EPP

Communication

- 56Kb Internal Modem
- TCP/IP Ethernet - SSL

CPU

- Cortex-A8 CPU (800MHz)
- DDR2 256MB SRAM memory
- 512MB Flash Memory
- Windows CE 6.0

Card Reader

- DIP Type card reader
- EMV Optional

ADA

- Voice Guidance
- Lighted Transaction Guidance

- Accessible Keypad Layout

Security

- UL291 Business Hours Vault
- Dial or Electronic Lock

Cash Dispenser

- 1000 Note Removable Cassette (SCDU)
- Up to 4 x 2000 Note Removable Cassette (HCDU)

Dimensions

- Height = 56.4"
- Width = 15.8"
- Depth = 22.3"
- Weight = 223 lbs. (Without cash dispenser)

Power Requirements

- 110/220 VAC $\pm 10\%$, 50/60 Hz, 145 Watts

Temperature Requirements

- In storage: 32°F - 104°F (0°C ~ 49°C)
- While operating: 45°F - 95°F (5°C ~ 35°C)

Allowable Humidity

- In storage : 10% < RH < 90%, non-condensed
- While operating : 15% < RH < 85%, non-condensed